



# MAXIMUM STORAGE TIME MAXIMUM SAFETY

## Standard Series

The body structure produced with a special technique provides resistance to tough impacts. Thanks to the double gasket applied to the cover and the tension lock mechanism, it prevents heat transfer and provides safe protection.

S Series products are suitable for transfers of approximately 15 hours. You can use the S Series, which works with 12/24 Volt energy, with solar panels. It is suitable for use in the storage of medical products, either fixed use in place or long-term transfers. With Coolermed Outdoor Coolers, you can set up mobile vaccine, medicine, serum and blood stations.



AC 200

AC 150

AC 100

AC 50

AC 25

<b>133</b> Liter	<b>+2 up to +8</b> Degree	<b>Solar Panel</b> 1 pieces SB200
<b>12/24</b> Volt	<b>12-19 Hour</b> Storage Time	<b>Battery pack bag</b> BB100



AC25/AC50/AC100/AC150/AC200 are certified as  
Class IIa Medical Devices according to Medical  
Device Directive (93/42/EEC)

according to DIN 58371



# AC 50

Gross volume (l)	133	
Storage time (+ 2 ° C / + 8 ° C)	12 / 19 hour	
Set temperature	+4	
Operating range	0+15 °C	
First cooling time (from 32 ° C + 4 ° C)	24 hour	
Climate zone	ST/T (25 / 43 ° C)	
Exterior dimentions W x D x H (mm)	836.5x853x975	
Interior dimentions W x D x H (mm)	531x512x566.5	
Packed dimentions W x D x H (mm)	880x900x1060	
Shipping weight (kg)	97	
Net weight (kg)	80	
Energy consumption (kwh / 24h)	0,62	
Refrigerant	R600a	
Control unit	Micro Processor	
Voltage	12 / 24V DC	
<b>Solar panel bag (2*100watt)</b>	<b>Optional</b>	<b>1xSB200</b>
<b>Battery pack bag</b>	<b>Optional</b>	<b>BB100</b>
<b>Circle Power</b>	<b>Optional</b>	<b>42 / 67 Hour</b>
<b>Voltage</b>	<b>Optional</b>	<b>220V AC 50 Hz</b>

# SB200



External dimensions W x D x H (mm)	1295x819x232
Open size W x D (mm)	1567 x 1267
Net weight (kg)	65





## BB100

External dimensions W x D x H (mm)	745x505x360
Net weight (kg)	50,5

## BB200

External dimensions W x D x H (mm)	745x505x360
Net weight (kg)	90

## BB300

External dimensions W x D x H (mm)	745x505x360
Net weight (kg)	121,5